


DG M TNS 275 (952 400)

Prewired complete unit consisting of a base part and plug-in protection modules
High discharge capacity due to heavy-duty zinc oxide varistors/spark gaps
High reliability due to "Thermo Dynamic Control" SPD monitoring device



Modular surge arrester for use in TN-S systems

Type	DG M TNS 275
Part No.	952 400
SPD according to EN 61643-11	Type 2
SPD according to IEC 61643-1	Class II
Nominal a.c. voltage (U _N)	230/400 V
Max. continuous operating a.c. voltage (U _C)	275 V
Nominal discharge current (8/20 μs) (I _n)	20 kA
Max. discharge current (8/20 μs) (I _{max})	40 kA
Voltage protection level (U _P)	≤ 1.25 kV
Voltage protection level at 5 kA (U _P)	≤ 1 kV
Response time (t _A)	≤ 25 ns
Max. mains-side overcurrent protection	125 A gL/gG
Short-circuit withstand capability for max. mains-side overcurrent protection	50 kArms
Temporary overvoltage (TOV) (U _T)	335 V / 5 sec.
TOV characteristic	withstand
Operating temperature range (T _U)	-40°C...+80°C
Operating state/fault indication	green / red
Number of ports	1
Cross-sectional area (min.)	1.5 mm² solid/flexible
Cross-sectional area (max.)	35 mm² stranded/25 mm² flexible
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor
Degree of protection	IP 20
Capacity	4 module(s), DIN 43880
Approvals	KEMA, VDE, UL, VdS
PU	1 pc(s)
Weight	443,000 g
Customs tariff number	85363030
GTIN	4013364108455

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.