

Product Datasheet: DEHNrail modular, multipole




DR M 4P 255 (953 400)


Four-pole surge arrester consisting of a base element and plug-in protection module
High discharge capacity due to heavy-duty zinc oxide varistor/spark gap combination
Energy coordination with other arresters of the Red/Line product family



Figure without obligation



Basic circuit diagram DR M 4P ... FM



Dimension drawing DR M 4P ... FM

Four-pole surge arrester consisting of a base part and plug-in protection module; FM version with floating remote signalling contact

Type	DR M 4P 255
Part No.	953 400
SPD according to EN 61643-11	Type 3
SPD according to IEC 61643-1	Class III
Nominal a.c. voltage (U_N)	230/400 V
Max. continuous operating a.c. voltage (U_C)	255/440 V
Nominal load current a.c. (I_L)	25 A
Nominal discharge current (8/20 μ s) (I_n)	3 kA
Total discharge current (8/20 μ s) [$L1+L2+L3+N-PE$] (I_{total})	8 kA
Combined impulse (U_{OC})	6 kV
Combined impulse [$L1+L2+L3+N-PE$] ($U_{OC total}$)	16 kV
Voltage protection level [$L-N$] (U_P)	≤ 1000 V
Voltage protection level [$L/N-PE$] (U_P)	≤ 1500 V
Response time [$L-N$] (t_A)	≤ 25 ns
Response time [$L/N-PE$] (t_A)	≤ 100 ns
Max. mains-side overcurrent protection	25 A gL/gG or B 25 A
Short-circuit withstand capability for mains-side overcurrent protection with 25 A gL/gG	6 kA _{rms}
Temporary overvoltage (TOV) [$L-N$] (U_T)	335 V / 5 sec.
Temporary overvoltage (TOV) [$L/N-PE$] (U_T)	400 V / 5 sec.
Temporary overvoltage (TOV) [$N-PE$] (U_T)	1200 V / 200 ms
TOV characteristic [$L-N$]	withstand
TOV characteristic [$L/N-PE$]	withstand
TOV characteristic [$L+N-PE$]	safe
Operating temperature range (T_U)	-40°C...+80°C
Operating state/fault indication	green / red
Number of ports	1
Cross-sectional area (min.)	0.5 mm ² solid/flexible
Cross-sectional area (max.)	4 mm ² stranded/2.5 mm ² flexible
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor
Degree of protection	IP 20
Capacity	2 mods., DIN 43880
Approvals, Certifications	KEMA, VDE, UL
PU	1 pc(s)
Weight	137,700 g
Customs tariff number	85363010
GTIN	4013364115767

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.