

ARCA 403021



Sample photo

Order symbol: ARCA 403021
Product nbr: 8120007
Description: Cabinet, PC
Remarks: Grey cover, 2-point locking, hinges on the long side

EAN: 6418074079183
El. number:
Finland: 3423054
Electric No. 8212091058
Denmark:
Electric No. Sweden: 2500114

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. F versions with flange opening. Door guide included.

Dimensions:			Accessories:		
Length	Width	Height	MPP ARCA 4030	Mounting plate perforated	
mm:	400	300	210	MPX ARCA 4030	Mounting plate
inch:	15.7	11.8	8.3	DRS ARCA 403015	DIN rail frame set
Materials:			DRS ARCA 403021	DIN rail frame set	
Material:	Polycarbonate		IDS ARCA 4030	Inner door set	
Base colour:	RAL 7035 -light grey		PMK ARCA 30	Pole mounting kit	
Cover colour:	RAL 7035 -light grey				
Gasket material:	Polyurethane				
Temperatures:			Rating:		
Temperature °C (short term):	-40 ... 120 °C		Ingress Protection (EN 60529): IP66		
Temperature °C (continuous):	-40 ... 80 °C		Impact Resistance (EN 62262): IK10 +35°C /IK08 -25°C		
Temperature °F (short term):	-40 ... 250 °F		Electrical insulation: Totally insulated		
Temperature °F (continuous):	-40 ... 175 °F		Halogen free (DIN/VDE 0472, Part 815): 1		
Accessories:			UV resistance: UL 508		
MPS ARCA 4030	Mounting plate		Glow Wire Test (IEC 695-2-1) °C: 960		
			Certificates:		
			SGS Fimko		
			Gost R		

