

Technical Data: Handles, Shafts and Extended Shafts for Enclosed and Door Interlocked BS88 Switched Fuse

A


Important Safety Notice 🗥

It is the responsibility of the person installing the electrical equipment to ensure that the installation meets the requirements of the IET wiring regulations and is therefore 'fit for purpose'. Factors such as correct selection of components, cable sizing, protective devices and Earth bonding are all critical and should be checked prior to full testing and power-up. Any other regulations applicable to the equipment being installed such as the Machinery Directive and current health and safety legislation must also be adhered to.

Terminals, including factory fitted, should be checked periodically to ensure correct tightness.

DO NOT USE POWER TOOLS ON THESE PRODUCTS

Product Prefix	Blue & White Handle	Red & Yellow Handle	Shaft Section (mm)	L (mm)	P (mm)	S (mm)	D (mm)
Standard Handle ar	nd Shafts						
LBF125/LBFD125	LBPHBW100	LBPHRY100	□7	250	165-282	94	
LBF160/LBFD160	LBPHBW020	LBPHRY020	□10	227	180-292	115	45
LBF200/LBFD200							
LBF315/LBFD315	LBPHBW040	LBPHRY040	- □14	239	216-286	176	
LBF400/LBFD400							
LBF630/LBFD630	LBPHBW050	LBPHRY050		186	235-286		60
LBF800/LBFD800							
Extended Shafts							
Product Prefix	Extended Shaft Type 1	Shaft Section (mm)	L (mm)	P (mm)	Extended Shaft Type 2	L (mm)	P (mm)
LBFD125	LBES020	□7	387	165-419	Not Available		
LBFD160	LBES030	□10	375	180-440	LBES040	536	180-601
LBFD200					LDE3U4U	550	
LBFD315	LBES050	□14	345	216-392	LBES060	535	216-582
LBFD400							
LBFD630				235-445			235-635
LBFD800							



P=DISTANCE FROM THE BACK OF THE SWITCH TO THE INSIDE OF THE PANEL

