

RAS-PB1534

Specifications and dimensions



- 22mm Twin Illuminated Pushbutton
- On - Off Configuration

Features	
Height	55mm
Width	30mm
Depth in front of panel	14mm
Depth behind panel with holder & contact	66mm
Weight	0.043Kg
Available colours	Red / Green
Standard	EN 60947-5-1
Degree of protection	IP40
Operating temperature	-25°C to +70°C
Mechanical life	10 ⁶ operations
Bezel construction	Bright metal (ZAMAC)
Related products	
Mounting collar (required)	RAS-FB
Direct connected lamp holder	RAS-LP6
Diode & series resistor lampholder	RAS-LP7
NO contact block	RAS-CBNO
NC contact block	RAS-CBNC
Legend plate	RB2-PY

ⓘ ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Information provided in data sheets and/or specifications may vary from actual results in different applications and performance may vary over time. **All products must be installed according to manufacturers instructions.**

Europa House, Airport Way, Luton, Beds, LU2 9NH Tel: 01582 692 440 / Fax: 01582 692 450 e-mail: sales@europacomponents.com
website: <http://www.europacomponents.com>