

RC1PBG4

Specifications and dimensions



- 2 position key switch enclosed
- Key removeable in both positions
- Plastic enclosure

| Features | |
|---------------------------------------|----------------------------|
| Height | 74mm |
| Width | 68mm |
| Depth | 51mm |
| Depth including head | 72mm |
| Depth including head and key inserted | 95mm |
| Weight | 0.19Kg |
| Colour | Grey lid on dark grey base |
| Enclosure construction | ABS plastic |
| Standard | EN 60947-5-1 |
| Degree of protection | IP65 |
| Operating temperature | -25°C to +70°C |
| Mechanical life | 10 ⁶ operations |
| Cable capacity of terminals | 2 x 1.5mm ² |
| Rated thermal current I _{th} | 10A |
| Switch reference | RP2-BG4 |
| Contact block reference | RAS-BCBNO |
| Related products | |
| NO contact block (plastic enc) | RAS-BCBNO |
| NC contact block (plastic enc) | RAS-BCBNC |
| Spare key | RB2-K455 |

ⓘ ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Information provided in data sheets and/or specifications may vary from actual results in different applications and performance may vary over time. **All products must be installed according to manufacturers instructions.**

Europa House, Airport Way, Luton, Beds, LU2 9NH Tel: 01582 692 440 / Fax: 01582 692 450 e-mail: sales@europacomponents.com
website: <http://www.europacomponents.com>