

This document must be retained for future reference.

It is the responsibility of the person installing the electrical equipment to ensure that the installation meets the requirements of the IET wiring regulations and is therefore 'fit for purpose'. Factors such as correct selection of components, cable sizing, protective devices and Earth bonding are all critical and should be checked prior to full testing and power-up. Any other regulations applicable to the equipment being installed such as the Machinery Directive and current health and safety legislation must also be adhered to.

All connections (including factory made) must be checked for the correct tightness prior to commissioning of the electrical installation.
All connections should also be inspected periodically to ensure correct tightness.

DO NOT USE POWER TOOLS ON THESE PRODUCTS



RM3GRG

Specifications and dimensions

- 3 Position pushbutton station
- 2 green pushbuttons and one red pushbutton
- Metal enclosure



| Features | |
|---------------------------------------|----------------------------|
| Length | 71mm |
| Width | 162mm |
| Depth | 88mm |
| Depth including head | 102mm |
| Depth including head and key inserted | 95mm |
| Weight | 0.51Kg |
| Colour | Grey lid on dark grey base |
| Enclosure construction | Die cast aluminium |
| Standard | EN 60947-5-1 |
| Degree of protection | IP65 |
| Operating temperature | -25°C to +70°C |
| Mechanical life | 10 ⁶ operations |
| Cable capacity of terminals | 2 x 1.5mm ² |
| Rated thermal current I _{th} | 10A |
| Green pushbutton reference | RCAS-BPF3 |
| Contact block reference | RAS-BCNO |
| Redpushbutton reference | RCAS-BPF4 |
| Contact block reference | RAS-BCNO |
| Related Products | |
| NO contact block | RAS-BCNOM |
| NC contact block | RAS-BCNCM |

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.