

This document must be retained for future reference.

It is the responsibility of the person installing the electrical equipment to ensure that the installation meets the requirements of the IET wiring regulations and is therefore 'fit for purpose'. Factors such as correct selection of components, cable sizing, protective devices and Earth bonding are all critical and should be checked prior to full testing and power-up. Any other regulations applicable to the equipment being installed such as the Machinery Directive and current health and safety legislation must also be adhered to.

All connections (including factory made) must be checked for the correct tightness prior to commissioning of the electrical installation. All connections should also be inspected periodically to ensure correct tightness.

DO NOT USE POWER TOOLS ON THESE PRODUCTS





STBDR1M

- TS35 Top Hat Din Rail
- Slotted



Features	
Length	1m
Width	35mm
Height	7.5mm
Weight	0.312Kg
Standard	DIN 46277
Construction	Cold Rolled Steel
Coating	Galvanised Zinc
Coating Thickness	> 8 microns
Slot Dimension	15mm x 6.3mm
Related Products	
Steel end clamp	CA302
Mounting bracket	CA603

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Information provided in data sheets and/or specifications may vary from actual results in different applications and performance may vary over time. All products must be installed according to manufacturers instructions.