

This document must be retained for future reference.

It is the responsibility of the person installing the electrical equipment to ensure that the installation meets the requirements of the IET wiring regulations and is therefore 'fit for purpose'. Factors such as correct selection of components, cable sizing, protective devices and Earth bonding are all critical and should be checked prior to full testing and power-up. Any other regulations applicable to the equipment being installed such as the Machinery Directive and current health and safety legislation must also be adhered to.

All connections (including factory made) must be checked for the correct tightness prior to commissioning of the electrical installation. All connections should also be inspected periodically to ensure correct tightness.

DO NOT USE POWER TOOLS ON THESE PRODUCTS



## RC1PBG4

### Specifications and dimensions

- 2 position key switch enclosed
- Key removeable in both positions
- Plastic enclosure



Features	
Height	74mm
Width	68mm
Depth	51mm
Depth including head	72mm
Depth including head and key inserted	95mm
Weight	0.19Kg
Colour	Grey lid on dark grey base
Enclosure construction	ABS plastic
Standard	EN 60947-5-1
Degree of protection	IP65
Operating temperature	-25°C to +70°C
Mechanical life	10 <sup>6</sup> operations
Cable capacity of terminals	2 x 1.5mm <sup>2</sup>
Rated thermal current I <sub>th</sub>	10A
Switch reference	RP2-BG4
Contact block reference	RAS-BCBNO
Related products	
NO contact block	RAS-BCBNO
NC contact block	RAS-BCBNC
Spare key	RB2-K455

**ⓘ ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.**

Information provided in data sheets and/or specifications may vary from actual results in different applications and performance may vary over time. **All products must be installed according to manufacturers instructions.**