

This document must be retained for future reference.

It is the responsibility of the person installing the electrical equipment to ensure that the installation meets the requirements of the IET wiring regulations and is therefore 'fit for purpose'. Factors such as correct selection of components, cable sizing, protective devices and Earth bonding are all critical and should be checked prior to full testing and power-up. Any other regulations applicable to the equipment being installed such as the Machinery Directive and current health and safety legislation must also be adhered to.

All connections (including factory made) must be checked for the correct tightness prior to commissioning of the electrical installation. All connections should also be inspected periodically to ensure correct tightness.

DO NOT USE POWER TOOLS ON THESE PRODUCTS



RCAS-ES542

Specifications and dimensions

- 22mm Red Mushroom Head Pushbutton
- Twist release operation
- Complete with NC contact



Features	
Diameter	40mm
Depth in front of panel	35mm
Depth behind panel (1 contact)	43mm
Weight	0.11Kg
Available colours	Red
Standard	EN 60947-5-1
Degree of protection	IP65
Operating temperature	-25°C to +70°C
Mechanical life	300,000 operations
Bezel construction	Bright metal (ZAMAC)
Contact Block	
Rated thermal current I _{th}	10A
Rated insulation voltage U _i	500V
Operating force	8N
Operating force additional contacts	3N
Cable capacity	2 x 1.5mm ²
Contact operation	Slow action, positive opening
Related Products	
Mounting collar (fitted)	RAS-FB
Single hole enclosure	RC-1MY
Single hole enclosure shrouded	RC-1MS
NO contact block	RAS-CBNO
NC contact block	RAS-CBNC
Legend plate	RB2-PY

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.