

This document must be retained for future reference.

It is the responsibility of the person installing the electrical equipment to ensure that the installation meets the requirements of the IET wiring regulations and is therefore 'fit for purpose'. Factors such as correct selection of components, cable sizing, protective devices and Earth bonding are all critical and should be checked prior to full testing and power-up. Any other regulations applicable to the equipment being installed such as the Machinery Directive and current health and safety legislation must also be adhered to.

All connections (including factory made) must be checked for the correct tightness prior to commissioning of the electrical installation. All connections should also be inspected periodically to ensure correct tightness.

DO NOT USE POWER TOOLS ON THESE PRODUCTS



RM2GES55

Specifications and dimensions

- 2 Position pushbutton station
- Green pushbutton and twist to release mushroom head
- Metal enclosure



Features	
Length	71mm
Width	162mm
Depth	88mm
Depth including head	109mm
Weight	0.51Kg
Colour	Grey lid on dark grey base
Enclosure construction	Die cast aluminium
Standard	EN 60947-5-1
Degree of protection	IP65
Operating temperature	-25°C to +70°C
Mechanical life	10 ⁶ operations
Cable capacity of terminals	2 x 1.5 mm ²
Rated thermal current I _{th}	10A
Green pushbutton reference	RCAS-BPF3
Contact block reference	RAS-BCNO
Red mushroom pushbutton reference	RCAS-ES54
Contact block reference	RAS-BCNC
Related products	
NO contact block	RAS-BCNO
NC contact block	RAS-BCNC

ⓘ ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Information provided in data sheets and/or specifications may vary from actual results in different applications and performance may vary over time. **All products must be installed according to manufacturers instructions.**